



- Corrosion-resistant stainless steel pump housing and impellers
- Automatic operation thanks to float switch
- Integrated non-return valve
- Min. draining level up to 2 mm thanks to flat suction device

Model: **CLEAROX 9/12**  
 Part number: **N1080140**  
 Barcode: **7630046619145**

Submersible pump for clear water drainage, equipped with float switch for automatic operation and with ergonomic handle for a secure grip and an easy portability. Thanks to cooling jacket the pump can work in both immersed and submerged conditions. The flat suction device allows to drain water down to 2mm



#### APPLICATIONS

Drainage of standing water and domestic waste water  
 Flooded rooms emptying and drying  
 Water drawing from wells, basins or cisterns

<b>ABSORBED POWER</b>	700 W	<b>MAX. IMMERSION DEPTH</b>	7 m
<b>VOLTAGE</b>	230 V	<b>MAX.TEMPERATURE OF PUMPED LIQUID</b>	35 °C
<b>FLOW RATE</b>	12.000 l/h	<b>MAX.SIZE OF IMPURITIES</b>	10 mm
<b>MAX. HEAD</b>	9 m	<b>START/STOP</b>	510 mm / 175 mm
<b>PUMP BODY</b>	Stainless steel	<b>WEIGHT</b>	5.8 kg
<b>PUMP OUTLET DIAMETER</b>	41,90 mm (1 1/4 F)	<b>PACKAGING DIMENSIONS</b>	24.7 x 20.5 x 36 cm
<b>MIN.PRIMING LEVEL</b>	21 mm	<b>PCS PER PALLET</b>	75
<b>MIN. DRAINING LEVEL</b>	2 mm with Flat suction device	<b>ACCESSORIES</b>	Flat Suction device