



- Energy saving thanks to higher hydraulic performances
- Dry running protection
- Self-priming pump
- Stainless steel pump body
- Pump longer life-time
- Protection against motor overload and
- Water temperature overheating


Model: **EVO-MULTIMAX
550 LOGIC SAFE**
 Part number: **N4501312**
 Barcode: **7630046621902**

Self priming surface pump with multistage hydraulic system and stainless steel pump body. EVO-MULTIMAX 550 LOGIC SAFE is equipped with LOGIC SAFE, an integrated electronic device for protection against dry running, motor overload and water temperature overheating.



APPLICATIONS

Irrigation of lawns and flowerbeds
 Washing of terraces or outdoors floors
 Basins or expansion tanks filling/draining

ABSORBED POWER	1350 W	POWER CABLE	1.5 m
VOLTAGE	230 V	SUCTION/DELIVERY PORT.	33.25 mm (1" F)
FLOW RATE	7800 l/h	MAX. ADVISED SUCTION HEAD	8 m
MAX. HEAD	62 m	WEIGHT	10.6 kg
RATED CURRENT	6 A	PACKAGING DIMENSIONS	43.3 x 23.6 x 25.3 cm
N° IMPELLERS	5	PCS PER PALLET	28
PROTECTION CLASS	IPX5	ACCESSORIES	-
PUMP BODY	Stainless Steel		x 5