



- Aluminium die-casting and stainless steel pump body
- Dry running protection by float switch
- Optimisation of hydraulic efficiency for high performance with lower energy consumption
- Ergonomic handle
- Made in Italy


Model: **SUB 330 S AUTO**  
 Part number: **N3016140**  
 Barcode: **7630046618087**

Submersible pump with asynchronous single phase motor with built-in thermal relay and stainless steel motor shaft. SUB 3S is equipped with float switch for automatic working and dry running protection.



### APPLICATIONS

- Irrigation of lawns and flowerbeds
- Washing of terraces or outdoors floors
- Basins or expansion tanks filling/drainage

<b>ABSORBED POWER</b>	650 W	<b>POWER CABLE</b>	10 m H07 RN8-F
<b>VOLTAGE</b>	230 V	<b>SUCTION/DELIVERY PORT.</b>	41.90 mm (1 1/4)
<b>FLOW RATE</b>	5600 l/h	<b>MAX.WATER TEMPERATURE</b>	40°C
<b>MAX.HEAD</b>	33 m	<b>WEIGHT</b>	7.4 kg
<b>RATED CURRENT</b>	3 A	<b>PACKAGING DIMENSIONS</b>	21.5 x 17 x 35.5 cm
<b>N° IMPELLERS</b>	3	<b>PCS PER PALLET</b>	48
<b>MIN.OPERATING SPACE</b>	500 mm	<b>ACCESSORIES</b>	
<b>MAX.IMMERSION DEPTH</b>	7 m		x 2