



- Alarm in case of low air pressure inside the tank (considering high number of pump start and stop)
- Dry running and motor overheating protection
- Function ART (Automatic Reset Test) : when the device is disconnected due to dry running it has been conceived to be able to automatically try to reconnect until the water is back in the system

Model: **DIGIPRESS**
 Part number: **ZB902570**
 Barcode: **7630046602185**

DIGIPRESS is an electronic pressure switch with an integrated digital pressure gauge.

It can manage the start and stop of single-phase electric pumps up to 2,2 Kw. Cut-in and cut-out pressure implementation can be set easily and accurately through user friendly control panel. It can operate as a differential pressure switch, as an inverted pressure switch, or just with max. or minimum pressures. DIGIPRESS includes also instantaneous current lecture, it controls and manages the overcurrent, the dry-running protection of the pump and fast cycling protection.



APPLICATIONS

- Surface pumps
- Submersible pumps

VOLTAGE	230 V	STARTING PRESSURE (CUT-IN)	0,5 ÷ 7 bar
RATED CURRENT	30 (16) A	STOPPING PRESSURE (CUT-OUT)	1 ÷ 8 bar
FREQUENCY	50/60 Hz	SUCTION / DELIVERY PORT	G 1/4" H
ABSORBED POWER	2.2 kW	MAX. WATER TEMPERATURE	50 C°
PROTECTION CLASS	IP 55	WEIGHT	0,28 Kg